



KINEMATIC VISCOSITY BATH

CONSTANT TEMPERATURE BATH(SOLID STATE) KINEMATIC VISCOSITY BATH: DIGITAL

Full Visibility. High precision. Stainless steel inner tank and outer of powder coated CR sheet. Toughened glass windows. Control of temp. By uP based digital fully solid state Prop.Controller with 3½ digit LED panel. Continuously variable 500 watts heater for greater accuracy. Boost heater cut-off automatically when not required. Pump to provide gentle yet through agitation of tank media. Temp. range 5°C above amb. to 120°C. Control Accuracy: ±0.01°C. Resolution 0.1°C Mains 230V, 50Hz AC.

CHAMBER SIZE			VOLUME	SUITABLE	POWER
L	W	D	LTR	FOR	(KW)
200	260	350	22	4 VM	1.50
370	260	350	40	6 VM	2.75



BATH WITH TRAY



REFRIGERATED VISCOSITY BATH

OPTIONAL ACCESSORIES

- Viscometers - Ostwald forward & reverse, Canonfensky, etc.
- Viscometer Stand
- Viscometer Tray
- Stop Watch
- High set safety cutoff device
- Resolution of 0.01°C with a 4 ½ digit LED display
- Lighting Attachment
- Coil for circulation of chilled water
- Pump Assembly for better uniformity
- Bath Media(for Temp. upto 120°C)
- Refrigetation system for below ambient temp. requirements
- Traceable Calibration Report



VISCOMETER STAND



GLASS VISCOMETERS



D-428, 10th Main, Peenya II Stage,
Peenya Industrial Area,
Bangalore-560058.
Telefax:091-080-23449007/23349239
Www.technoinstruments.co.in
email:ticci80@gmail.com